NSN 5930-00-776-2767

Sensitive Switch - Page 1 of 2

Between 0.517 inches and 0.523 inches

Body Style:Hole mounted

Body Length: 1.250 inches Body Width:



View Online at https://aerobasegroup.com/nsn/5930-00-776-2767

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches
Body Height:
0.500 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.101 inches and 0.104 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.309 inches and 0.315 inches
Actuator Length:
0.297 inches
Actuator Style:
Rectangular
Actuator Height:
0.094 inches
Actuator Width:
0.250 inches
Actuator Free Position Height:
0.187 inches
Maximum Voltage Rating In Volts:
125.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
15.0 ounces
Actuator Movement:
Between 0.140 pretravel inches and 0.015 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 10.000 amperes resistive ac
Terminal Type And Quantity:
3 tab, solder lug

NSN 5930-00-776-2767

Sensitive Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0