

View Online at <https://aerobasegroup.com/nsn/5930-00-777-6543>

Inside Diameter:

0.250 inches all connections

Overall Length:

4.656 inches

Overall Height:

1.906 inches

Overall Width:

5.312 inches

Body Length:

2.656 inches

Body Height:

1.834 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Longest Horizontal Distance Between Mounting Centers:

1.812 inches

Shortest Horizontal Distance Between Mounting Centers:

0.906 inches

Longest Vertical Distance Between Mounting Centers:

4.506 inches

Pressure Switch Type:

Differential

Mounting Method:

Base and unthreaded hole

Features Provided:

Capillary tube end seal connection

Thready Qty Per Inch (tpi):

18 all pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

4.6 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+450.00 actuation point pounds per square inch and +0.00/+450.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

Contact Stimulus Rating:

50.00 actuation point pounds per square inch and 290.00 actuation point pounds per square inch and 10.00 differential point pounds per square inch and 65.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

240.0 dc at sea level third voltage

Pressure Connector Type:

Swivel nut, gasket seal, threaded internal all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Ptf-sae short all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0