

View Online at <https://aerobasegroup.com/nsn/5930-00-777-6879>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.470 inches

Body Length:

0.840 inches

Body Width:

1.312 inches

Body Height:

0.946 inches

Actuator Style:

Round

Actuator Diameter:

0.428 inches

Actuator Height:

1.180 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

Sturgeon class ssn (637), underwater torpedo tubes, submarine ship control and navigation systems, submarine interior communication system, submarine communications and antenna systems

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0