

View Online at <https://aerobasegroup.com/nsn/5930-00-777-7331>

**Overall Length:**

Between 2.369 inches and 2.442 inches

**Body Length:**

Between 1.062 inches and 1.125 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.234 inches and 0.266 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.812 inches

**Longest Vertical Distance Between Mounting Centers:**

0.790 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Flange and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

1.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

7.50 actuation point pounds per square inch gage and 5.50 deactuation point pounds per square inch gage and 2.50 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0