

View Online at <https://aerobasegroup.com/nsn/5930-00-777-7331>

Overall Length:

Between 2.369 inches and 2.442 inches

Body Length:

Between 1.062 inches and 1.125 inches

Unthreaded Mounting Hole Diameter:

Between 0.234 inches and 0.266 inches

Longest Horizontal Distance Between Mounting Centers:

2.812 inches

Longest Vertical Distance Between Mounting Centers:

0.790 inches

Pressure Switch Type:

Gage

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

1.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

7.50 actuation point pounds per square inch gage and 5.50 deactuation point pounds per square inch gage and 2.50 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0