

NSN 5930-00-778-2139 Rotary Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-778-2139 **Overall Length:** 6.312 inches First Flat Length: 0.500 inches single actuator Flat Height: 0.312 inches single actuator **Shaft Diameter:** 0.375 inches single actuator **Shaft Length:** 0.687 inches single actuator

**Overall Diameter:** 

3.781 inches

**Individual Section Quantity:** 

**Knob Manufacturer Code:** 

04009

**Longest Horizontal Distance Between Mounting Centers:** 

3.218 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:** 

3.218 inches single mounting facility

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 each section front

**Throw Quantity:** 

4 each section front

**Mounting Method:** 

Threaded bushing single mounting facility

**Features Provided:** 

Actuator knob

Thready Qty Per Inch (tpi):

20 single mounting facility

**Thread Size:** 

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:** 

500.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:** 

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

4 single actuator

**Shaft Type:** 

Round, flatted, threaded hole single actuator

## NSN 5930-00-778-2139

Rotary Switch - Page 2 of 2

Fiig: A052b0



Terminal Type:
Tab w/screw
Contact Switching Action:
Makes before breaks, breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
10.0 amperes resistive load highest ac voltage rating at sea level
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No