

View Online at <https://aerobasegroup.com/nsn/5930-00-779-1065>

Body Style:

Hole mounted

Overall Length:

0.800 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Height:

1.076 inches

Overall Width:

0.260 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.356 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.562 inches

Actuator Roller Diameter:

0.187 inches

Actuator Roller Width:

0.125 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

7.0 ounces

Actuator Movement:

Between 0.219 pretravel inches and 0.030 overtravel inches and 0.025 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0