

View Online at <https://aerobasegroup.com/nsn/5930-00-779-2484>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

3.406 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.562 inches single actuator

**Overall Diameter:**

4.625 inches

**Individual Section Quantity:**

3

**Knob Manufacturer Code:**

10001

**Knob Manufacturer Part Number:**

S6202-74000-4

**End Application:**

An/sps-40e radar; iwo jima class lph; mine countermeasures support (mcs) class (lph-12); radar, search, an/sps-40; wasp class lhd; blue ridge class lcc-19; whidbey island class lsd; austin ship class lpd-4 amphibious transport docks; spruance class dd (963); tarawa class lha

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Mounting Facility Circle Radius:**

4.500 inches single mounting facility

**Mounting Method:**

Threaded hole single mounting facility

**Features Provided:**

Actuator knob and metallic inclosure

**Thready Qty Per Inch (tpi):**

16 single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

120.0 ac at sea level

**Mounting Facility Pattern:**

Three position circular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Special Features:**

Weapon system essential

**Style Designator:**

Snap or line

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0