

View Online at <https://aerobasegroup.com/nsn/5930-00-779-2484>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

3.406 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.562 inches single actuator

Overall Diameter:

4.625 inches

Individual Section Quantity:

3

Knob Manufacturer Code:

10001

Knob Manufacturer Part Number:

S6202-74000-4

End Application:

An/sps-40e radar; iwo jima class lph; mine countermeasures support (mcs) class (lph-12); radar, search, an/sps-40; wasp class lhd; blue ridge class lcc-19; whidbey island class lsd; austin ship class lpd-4 amphibious transport docks; spruance class dd (963); tarawa class lha

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Facility Circle Radius:

4.500 inches single mounting facility

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Thready Qty Per Inch (tpi):

16 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

120.0 ac at sea level

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Special Features:

Weapon system essential

Style Designator:

Snap or line

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0