

View Online at <https://aerobasegroup.com/nsn/5930-00-779-3627>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

2.751 inches

Overall Height:

1.312 inches

Overall Width:

1.281 inches

Shaft Diameter:

0.375 inches 1st actuator

Shaft Length:

1.219 inches 2nd actuator

Nonturn Device Radius:

0.531 inches at 3:00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

4 1st section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 2nd actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees 2nd actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Special Features:

Switch is supplied with coupling hairpin, 1 dummy terminal on rear of sect 2 and an outer shaft with an inner hole through to provide a free running inner shaft

Precious Material And Location:

Rotor blades and contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0