NSN 5930-00-779-3999

Rotary Switch - Page 1 of 2



| Rolary Switch - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5930-00-779-3999 |
| Thread Class: |
| 2b single mounting facility |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 7.625 inches |
| Overall Height: |
| 5.250 inches |
| Overall Width: |
| 4.500 inches |
| First Flat Length: |
| 0.875 inches single actuator |
| Flat Height: |
| 0.250 inches single actuator |
| Shaft Diameter: |
| 0.375 inches single actuator |
| Shaft Length: |
| 1.250 inches single actuator |
| Individual Section Quantity: |
| 5 |
| Knob Manufacturer Code: |
| 82121 |
| Knob Manufacturer Part Number: |
| A |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section rear |
| Throw Quantity: |
| 2 each section rear |

Mounting Facility Circle Radius:

1.109 inches single mounting facility

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

20 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

500.0 ac at sea level

NSN 5930-00-779-3999

Rotary Switch - Page 2 of 2



Mounting Facility Pattern: Four position circular single mounting facility **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** Round, flatted, threaded hole single actuator **Terminal Type:** Threaded stud **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 90.0 degrees single actuator **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 30.0 amperes resistive load ac at sea level **Style Designator:** Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A052b0