NSN 5930-00-779-7524

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-779-7524

Thread Class:
2a single mounting facility
Thread Length:
0.340 inches single mounting facility
Hazardous Locations/environmental Protection:
Fungus resistant and humidity resistant and salt spray resistant and shock resistant and vibration resistant
Overall Length:
2.960 inches
Overall Height:
1.280 inches
Overall Width:
0.925 inches
Shaft Diameter:
0.120 inches single actuator and 0.125 inches single actuator
Shaft Length:
1.000 inches single actuator
Individual Section Quantity:
4
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Switch Contact Basic Design:
Coded
Mounting Method:
Threaded bushing single mounting facility
Thread Size:
0.250 inches single mounting facility
Contact Voltage Rating In Volts:
250.0 ac at sea level
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Turret
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:

Contact Arrangement Truth Table:

11.0 amperes inductive load ac at sea level

Special each section

NSN 5930-00-779-7524

Rotary Switch - Page 2 of 2



	Special	Truth	Table	Identification
--	---------	--------------	--------------	----------------

91929-special 1-2-3-4 each section

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0