

View Online at <https://aerobasegroup.com/nsn/5930-00-779-9843>

Thread Class:

2a

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.812 inches

Body Length:

2.062 inches

Body Width:

0.930 inches

Body Height:

1.862 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.410 inches and 0.430 inches

Actuator Height:

0.705 inches

Actuator Free Position Height:

0.780 inches

Maximum Voltage Rating In Volts:

120.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

Between 16.0 ounces and 48.0 ounces

Switch Actuating Force:

Between 32.0 ounces and 96.0 ounces

Actuator Movement:

0.075 pretravel inches and 0.175 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes resistive ac

Thread Series Designator:

Unf

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0