

View Online at <https://aerobasegroup.com/nsn/5930-00-780-5517>

Thread Class:

2a single mounting facility

Thread Length:

0.190 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof and explosion proof

Overall Length:

3.250 inches

Overall Height:

2.500 inches

Overall Width:

2.438 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.250 inches single actuator

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

2.312 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.156 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.312 inches single mounting facility

Shortest Vertical Distance Between Mounting Centers:

1.156 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded stud single mounting facility

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position diamond single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, hollowed single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0