

View Online at <https://aerobasegroup.com/nsn/5930-00-780-8855>

Inside Diameter:

0.250 inches all connections

Overall Length:

8.219 inches

Overall Height:

2.656 inches

Overall Width:

3.594 inches

Body Length:

3.469 inches

Body Height:

2.656 inches

Unthreaded Mounting Hole Diameter:

0.266 inches

Longest Horizontal Distance Between Mounting Centers:

2.719 inches

Longest Vertical Distance Between Mounting Centers:

2.719 inches

End Application:

Kilauea class t-ae 26, systems, 02n2, forrestal class cv, hayes class t-ag 195, I.P. Compressors, nimitz class cvn

Pressure Switch Type:

Differential

Mounting Method:

Base and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 all pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Terminal Type:

Screw

Contact Load Current Rating:

6.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.00/+200.00 actuation point pounds per square inch and +0.00/+200.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

600.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded internal all connections

Special Features:

Weapon system essential

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Nptf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0