## NSN 5930-00-780-8863

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-780-8863

**Thread Class:** 

2b single mounting facility

**Hazardous Locations/environmental Protection:** 

Shock resistant and vibration resistant

**Overall Length:** 

**4.375** inches

**Overall Height:** 

2.219 inches

**Overall Width:** 

2.750 inches

**Individual Section Quantity:** 

**Knob Manufacturer Code:** 

82121

**Knob Manufacturer Part Number:** 

01040-1

**Longest Horizontal Distance Between Mounting Centers:** 

1.641 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:** 

1.641 inches single mounting facility

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:** 

Actuator knob and dummy section

Thready Qty Per Inch (tpi):

24 single mounting facility

**Thread Size:** 

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

350.0 highest dc voltage rating at sea level

**Mounting Facility Pattern:** 

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

4 single actuator

**Terminal Type:** 

Tab w/screw

**Switch Actuator Positioning Increment:** 

90.0 degrees single actuator

**Contact Load Current Rating:** 

10.0 amperes resistive load lowest dc voltage rating at sea level

## NSN 5930-00-780-8863

Rotary Switch - Page 2 of 2



Style	De	sia	nato	r:
	-	9.9	···	

Tap, circuit selector

## **Thread Series Designator:**

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0