

View Online at <https://aerobasegroup.com/nsn/5930-00-781-1957>

Thread Class:

3a single pressure connection

Overall Length:

3.380 inches

Overall Diameter:

1.000 inches

Pressure Switch Type:

Differential

Width Across Flats:

0.688 inches

Operating Temperature Rating:

Between -22.0 degrees fahrenheit and 260.0 degrees fahrenheit

Mounting Method:

Clamp

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Decrease

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage and 2.5 amperes inductive load single voltage and 500.0 milliamperes lamp load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+60.00 actuation point pounds per square inch gage and +0.00/+60.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point hex nut and external actuation point hex nut

Contact Stimulus Rating:

8.00 actuation point pounds per square inch gage and 42.10 deactuation point pounds per square inch gage and 34.10 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0