## NSN 5930-00-781-3403

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-781-3403

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Moisture resistant
Overall Length:
1.000 inches
Overall Height:
3.093 inches
Overall Width:
0.750 inches
Body Length:
0.905 inches
Body Width:
0.750 inches
Case Material:
Metal
Actuator Length:
0.680 inches
Actuator Style:
Rectangular
Actuator Height:
0.180 inches
Actuator Width:
0.430 inches
Actuator Color:
Green and white single actuator
Illuminated Actuator Color:
Green and white single actuator
Actuator Inscription:
Channel, 2 single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Holding solenoid
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes resistive ac

**Precious Material And Location:** 

Contact surfaces gold and contacts silver

## NSN 5930-00-781-3403

Push Switch - Page 2 of 2



ш	Inal	nia	-10	110	$\cdot$	MO.
u	, na	UIC		$\boldsymbol{\nu}$		uc.

Unable to decode and unable to decode

**Terminal Type And Quantity:** 

17 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0