NSN 5930-00-781-3405

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style: Panel mount

Moisture resistant
Overall Length:
1.000 inches
Overall Height:
3.093 inches



View Online at https://aerobasegroup.com/nsn/5930-00-781-3405

Overall Width:				
0.750 inches				
Body Length:				
0.905 inches				
Body Width:				
0.750 inches				
Case Material:				
Metal				
Actuator Length:				
0.680 inches				
Actuator Style:				
Rectangular				
Actuator Height:				
0.180 inches				
Actuator Width:				
0.430 inches				
Actuator Color:				
Green and white single actuator				
Illuminated Actuator Color:				
Green and white single actuator				
Actuator Inscription:				
Channel, 4 single actuator				
Maximum Voltage Rating In Volts:				
115.0 ac and 28.0 dc				
Inclosure Type:				
Fully enclosed				
Mounting Method:				
Panel				
Features Provided:				
Full display lens				
Nonpile-up Contact Arrangement:				
4 pole, double throw, one position momentary single switch unit				
Contact Load Current Rating At Maximum Rated Voltage:				
3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes resistive ac				

NSN 5930-00-781-3405

Push Switch - Page 2 of 2



Precious	Material	And I	Location:
riccious	waterial	Allu	LUCALIUII.

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

17 tab, solder lug

Shelf Life:

Unit Of Measure:

N/a

Demilitarization:

No

Fiig:

A053a0