

View Online at <https://aerobasegroup.com/nsn/5930-00-781-3452>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Fungus proof and moisture proof

**Bushing Length:**

0.375 inches

**Body Length:**

2.812 inches

**Body Width:**

1.250 inches

**Body Height:**

1.625 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.438 inches

**Actuator Height:**

1.250 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position locked in

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

125.0 ac

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

20

**Pile-up Contact Form Arrangement:**

2b1c 1st position

**Thread Size:**

0.250 inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

7 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0