NSN 5930-00-781-6774

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-781-6774

| Body Style: |
|--|
| Bushing mounted |
| Hazardous Locations/environmental Protection: |
| Corrosion resistant |
| Overall Length: |
| 2.400 inches |
| Body Diameter: |
| 1.015 inches |
| Bushing Length: |
| 0.860 inches |
| Body Length: |
| 1.200 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.250 inches |
| Actuator Height: |
| 0.380 inches |
| Actuator Free Position Height: |
| 1.380 inches |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 64.0 ounces |
| Switch Actuating Force: |
| 144.0 ounces |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes motor dc |
| Special Features: |
| Unthreaded bushing flange mounted |
| Terminal Type And Quantity: |
| 6 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5930-00-781-6774

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0