

View Online at <https://aerobasegroup.com/nsn/5930-00-782-1891>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Unthreaded Mounting Hole Diameter:

0.139 inches

Actuator Length:

1.938 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

1.188 inches

Actuator Roller Diameter:

0.370 inches

Actuator Roller Width:

0.150 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

End Application:

Lgm-30 minuteman missile.

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.5 ounces

Switch Actuating Force:

6.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.083 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0