NSN 5930-00-783-7211

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-783-7211

Thread Class: 2b 1st mounting facility Thread Length: 0.375 inches 2nd mounting facility **Overall Length:** 8.900 inches **Overall Height:** 2.812 inches **Overall Width:** 2.812 inches **Shaft Length:** 1.275 inches single actuator **Individual Section Quantity:** 14 **Knob Manufacturer Code:** 82121 **Knob Manufacturer Part Number:** Α **Knob Specificationial Markings:** Marked with arrow **Longest Horizontal Distance Between Mounting Centers:** 2.297 inches 1st mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.297 inches 1st mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 15 each section rear **Mounting Facility Circle Radius:** 0.906 inches 2nd mounting facility **Mounting Method:** Threaded stud 2nd mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 1st mounting facility **Thread Size:** 0.190 inches 2nd mounting facility

125.0 ac at sea level

Contact Voltage Rating In Volts:

NSN 5930-00-783-7211Rotary Switch - Page 2 of 2



Mounting Facility Pattern:
Four position circular 1st mounting facility
Switch Actuator Indexing Position Quantity:
16 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator
Square Shaft Size:
0.250 inches single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
22.5 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load ac at sea level
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unf 2nd mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0