NSN 5930-00-784-0947

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-784-0947

Thread Class:

2b single mounting facility

Overall Length:

3.730 inches

Overall Height:

1.609 inches

Overall Width:

1.560 inches

First Flat Length:

0.560 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.248 inches single actuator

Shaft Length:

0.730 inches single actuator

Individual Section Quantity:

6

Longest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Cam actuated

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

45.0 degrees from contact position 1 single actuator

Mounting Facility Pattern:

Two position in-line single mounting facility

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, one position momentary each switch each section in-line

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

NSN 5930-00-784-0947 Rotary Switch - Page 2 of 2



Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section in-line
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load dc at sea level
Style Designator:
In-line, cam actuated
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0