

View Online at <https://aerobasegroup.com/nsn/5930-00-784-1589>

Thread Class:

3a single pressure connection

Overall Length:

3.400 inches

Outside Diameter:

0.562 inches single connection

Body Length:

2.844 inches

Overall Diameter:

1.000 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -0.0 degrees celsius and 45.0 degrees celsius

Mounting Method:

Inlet connection

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

6000.00 pounds per square inch gage

Thread Size:

0.562 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

10000.00 pounds per square inch

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

750.00 actuation point pounds per square inch gage and 550.00 deactuation point pounds per square inch gage and 200.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

110.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0