

View Online at <https://aerobasegroup.com/nsn/5930-00-784-3278>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

1.015 inches

Overall Width:

0.688 inches

Body Length:

1.250 inches

Body Width:

0.500 inches

Body Height:

0.890 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Actuator Length:

0.250 inches

Actuator Style:

Rectangular

Actuator Height:

0.125 inches

Actuator Width:

0.297 inches

Actuator Free Position Height:

0.562 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Integral

Nonpile-up Contact Arrangement:

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

17.0 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.015 overtravel inches and 0.028 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0