

View Online at <https://aerobasegroup.com/nsn/5930-00-784-3278>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

1.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Overall Height:**

1.015 inches

**Overall Width:**

0.688 inches

**Body Length:**

1.250 inches

**Body Width:**

0.500 inches

**Body Height:**

0.890 inches

**Unthreaded Mounting Hole Diameter:**

0.114 inches

**Actuator Length:**

0.250 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.125 inches

**Actuator Width:**

0.297 inches

**Actuator Free Position Height:**

0.562 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Integral

**Nonpile-up Contact Arrangement:**

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

17.0 ounces

**Actuator Movement:**

Between 0.060 pretravel inches and 0.015 overtravel inches and 0.028 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0