NSN 5930-00-784-4206

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-784-4206

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.500 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.438 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.125 inches
Actuator Style:
Rectangular
Actuator Height:
0.093 inches
Actuator Width:
0.125 inches
Actuator Free Position Height:
0.437 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
2.0 ounces
Switch Actuating Force:
Between 3.0 ounces and 5.0 ounces
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000
amperes inductive ac and 3.000 amperes lamp ac
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

__

NSN 5930-00-784-4206

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0