NSN 5930-00-784-7909

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-784-7909 **Thread Class:** 2a **Body Style:** Hole mounted **Overall Length:** 3.812 inches Center To Center Distance Between Mounting Facilities Parallel To Width: Between 0.432 inches and 0.442 inches **Overall Height:** 1.125 inches **Overall Width:** 0.750 inches **Body Length:** Between 2.234 inches and 2.266 inches **Body Width:** Between 0.745 inches and 0.755 inches **Body Height:** Between 1.109 inches and 1.141 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.870 inches and 0.880 inches **Actuator Style:** Round **Actuator Diameter:** Between 0.359 inches and 0.391 inches **Actuator Height:** Between 1.234 inches and 1.266 inches **Actuator Position-action Relationship:** Up position momentary and down position momentary and center position maintained **Maximum Voltage Rating In Volts:** 110.0 ac **Inclosure Type:** Uninclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): **Pile-up Contact Form Arrangement:** 1a1b1c single position

Thread Size:

0.086 inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive ac

NSN 5930-00-784-7909

Lever Switch - Page 2 of 2



Thread Series Designator:
Unc
Terminal Type And Quantity:
7 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0