

View Online at <https://aerobasegroup.com/nsn/5930-00-784-8989>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

2.563 inches

Overall Height:

1.875 inches

Overall Width:

1.812 inches

First Flat Length:

0.620 inches single actuator

Flat Height:

0.208 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.626 inches single actuator

Nonturn Device Radius:

0.469 inches at 9: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

27 single mounting facility

Thread Size:

0.393 inches single mounting facility

Contact Voltage Rating In Volts:

480.0 highest ac voltage rating at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, slotted, flatted single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

35.0 amperes resistive load lowest ac voltage rating at sea level

Style Designator:

Rectangular panel mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0