NSN 5930-00-785-4108

Rotary Switch - Page 1 of 2

0.469 inches single mounting facility

Hazardous Locations/environmental Protection:

Thread Class:

Thread Length:

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-785-4108

Dustproof			
Overall Length:			
3.344 inches			
Overall Diameter:			
2.000 inches			
Individual Section Quantity:			
3			
Knob Manufacturer Code:			
80064			
Knob Manufacturer Part Number:			
74000-2			
Switch Contact Basic Design:			
Nonpile-up symmetrical			
Pole Quantity:			
1 each section front			
Throw Quantity:			
7 single section front			
Mounting Method:			
Threaded bushing single mounting facility			
Features Provided:			
Actuator knob			
Thready Qty Per Inch (tpi):			
32 single mounting facility			
Thread Size:			
0.469 inches single mounting facility			
Contact Voltage Rating In Volts:			
125.0 ac at sea level			
Switch Actuator Indexing Position Quantity:			
8 single actuator			
Terminal Type:			
Tab w/screw			
Contact Switching Action:			
Breaks before makes each section front			
Switch Actuator Positioning Increment:			
45.0 degrees single actuator			
Switch Actuator Stop Device Type:			

Adjustable stop single actuator

NSN 5930-00-785-4108

Rotary Switch - Page 2 of 2



Contact	l oad	Current	Rating:
CUIIIACI	∟∪au	Guileiii	naumu.

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0

Mil-std (military Standard):

Mil-s-21604 spec.