NSN 5930-00-785-8347

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-785-8347

Thread Class: 2b single mounting facility **Overall Length:** 4.690 inches **Overall Height:** 2.250 inches **Overall Width:** 2.570 inches First Flat Length: 0.560 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 2.750 inches single actuator **Unthreaded Mounting Hole Diameter:** 0.164 inches single mounting facility **Individual Section Quantity:** 1 **Longest Horizontal Distance Between Mounting Centers:** 1.500 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 4 single section periphery **Throw Quantity:** 3 single section periphery **Mounting Method:** Bracket single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Contact Voltage Rating In Volts:** 118.0 ac at sea level **Mounting Facility Pattern:** Two position in-line single mounting facility **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** Round, v flatted single actuator **Terminal Type:**

Turret

NSN 5930-00-785-8347

Rotary Switch - Page 2 of 2



_		
Contact	Switching	Action:
JUIIIALI	Switching	ACLIOII.

Breaks before makes single section periphery

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level

Special Features:

Crosstalk shall not exceed 40db down with 2000 ohms between terminals and ground and a 2v rms 2 kc signal applied to any terminal

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0