## NSN 5930-00-786-8436

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-786-8436

Body Style:
Hole mounted
Overall Length:
2.375 inches
Overall Height:
2.645 inches
Overall Width:
1.109 inches
Actuator Length:
0.641 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.310 inches
Actuator Roller Diameter:
0.375 inches
Actuator Roller Width:
0.125 inches
Housing Length:
1.625 inches
Housing Width:
1.109 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.335 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.094 inches
Maximum Voltage Rating In Volts:
30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
15.0 ounces
Switch Actuating Force:
96.0 ounces
Actuator Movement:
Between 0.085 pretravel inches and 0.187 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive dc and 10.000 amperes inductive dc

## **NSN 5930-00-786-8436** Sensitive Switch - Page 2 of 2



<b>Precious Material And Location:</b>
All metal parts surfaces silver
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0