

View Online at <https://aerobasegroup.com/nsn/5930-00-787-7481>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

0.800 inches

Body Width:

0.400 inches

Body Height:

0.295 inches

Unthreaded Mounting Hole Diameter:

0.100 inches

Actuator Length:

0.218 inches

Actuator Height:

0.328 inches

Actuator Width:

0.125 inches

Actuator Position-action Relationship:

Center position maintained and left position maintained and right position maintained

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 115.0 dc

End Application:

Gwhidbey island class lsd, support equipment for b-52 aircraft, oliver perry class ffg, tarawa class lha, nimitz class cvn, forrestal class cv, virginia class cg (41), supply clase aoe, spruance class dd(963)

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

0.500 amperes resistive dc and 0.500 amperes resistive ac

Special Features:

Weapons system essential

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0