## NSN 5930-00-788-3135

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-788-3135

Thread Length:

0.250 inches single mounting facility

First Flat Length:

0.375 inches single actuator

Flat Height:

0.218 inches single actuator

**Shaft Diameter:** 

0.281 inches single actuator

**Shaft Length:** 

0.781 inches single actuator

**Individual Section Quantity:** 

3

**Switch Contact Basic Design:** 

Nonpile-up symmetrical and nonpile-up nonsymmetrical

**Pole Quantity:** 

1 3rd section front

**Throw Quantity:** 

7 1st section front

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Rotor Through Connection Quantity:** 

1 each section

**Switch Actuator Indexing Position Quantity:** 

7 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Makes before breaks each section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Contact Load Current Rating:** 

1.0 amperes resistive load ac at sea level

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

## **NSN 5930-00-788-3135** Rotary Switch - Page 2 of 2



|    | • • |    |    |    |     |    |    |
|----|-----|----|----|----|-----|----|----|
| ın | 18  | Of | ΝЛ | ດລ | CI. | ır | ο. |
|    |     |    |    |    |     |    |    |

Demilitarization:

No

Fiig:

A052b0