

View Online at <https://aerobasegroup.com/nsn/5930-00-788-7449>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

5.375 inches

**Overall Height:**

1.500 inches

**Overall Width:**

1.312 inches

**First Flat Length:**

0.375 inches single actuator

**Flat Height:**

0.216 inches single actuator and 0.220 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.875 inches single actuator

**Individual Section Quantity:**

8

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section rear

**Throw Quantity:**

5 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

15.0 dc at sea level

**Shaft Flat/slot Angular Location:**

225.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+2.000/+6.000 inch-pounds single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

2.0 milliamperes resistive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0