

View Online at <https://aerobasegroup.com/nsn/5930-00-789-2255>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

11.180 inches

Overall Height:

4.750 inches

Overall Width:

4.750 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.312 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.000 inches single actuator

Unthreaded Mounting Hole Diameter:

0.406 inches 2nd mounting facility and 0.410 inches 2nd mounting facility

Individual Section Quantity:

11

Knob Manufacturer Code:

80064

Knob Manufacturer Part Number:

9s536316

Longest Horizontal Distance Between Mounting Centers:

3.781 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

3.781 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

2 each section rear

Mounting Method:

Unthreaded hole 1st mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0