NSN 5930-00-789-5042

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-789-5042

| Center To Center Distance Between Mounting Facilities Parallel To Length: |
|--------------------------------------------------------------------------------------------------------------------------------------|
| 2.125 inches |
| Body Length: |
| 2.500 inches |
| Body Width: |
| 0.828 inches |
| Body Height: |
| 1.031 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.344 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.250 inches |
| Maximum Voltage Rating In Volts: |
| 600.0 ac and 600.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Nonpile-up Contact Arrangement: |
| 1 two circuit, double break/double make, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 20.000 milliamperes resistive dc and 20.000 milliamperes inductive dc and 15.000 amperes resistive ac and 5.000 amperes inductive ac |
| Terminal Type And Quantity: |
| 4 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A053a0 |
| |
| |