

View Online at <https://aerobasegroup.com/nsn/5930-00-789-6089>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

1.140 inches

**First Flat Length:**

0.230 inches single actuator and 0.270 inches single actuator

**Flat Height:**

0.214 inches single actuator and 0.224 inches single actuator

**Shaft Diameter:**

0.332 inches single actuator

**Shaft Length:**

0.292 inches single actuator

**Overall Diameter:**

Between 0.938 inches and 1.062 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

7 single section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

6.0 lowest dc voltage rating at sea level

**Shaft Flat/slot Angular Location:**

36.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section front

**Switch Actuator Positioning Increment:**

40.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

250.0 milliamperes inductive load ac at sea level and 1.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0