NSN 5930-00-789-6268

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-789-6268

| Thread Class: |
|---|
| 2a |
| Body Style: |
| Bushing mounted |
| Overall Length: |
| 2.355 inches |
| Overall Height: |
| 1.000 inches |
| Overall Width: |
| 1.000 inches |
| Body Diameter: |
| 1.000 inches |
| Bushing Length: |
| 1.000 inches |
| Body Length: |
| 0.980 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.250 inches |
| Actuator Height: |
| 0.375 inches |
| Actuator Free Position Height: |
| 1.375 inches |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thread Size: |
| 0.625 inches |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 64.0 ounces |
| Switch Actuating Force: |
| 144.0 ounces |
| Actuator Movement: |

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes motor dc

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

NSN 5930-00-789-6268

Sensitive Switch - Page 2 of 2



| Special Features: |
|-----------------------------|
| 68 in. Lg wire leads |
| Thread Series Designator: |
| Unef |
| Terminal Type And Quantity: |
| 6 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0