

View Online at <https://aerobasegroup.com/nsn/5930-00-789-6714>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.810 inches

**Overall Height:**

2.670 inches

**Overall Width:**

2.670 inches

**First Flat Length:**

0.690 inches single actuator

**Shaft Diameter:**

0.890 inches single actuator

**Shaft Length:**

2.310 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.260 inches single mounting facility and 0.270 inches single mounting facility

**Individual Section Quantity:**

1

**Knob Manufacturer Code:**

16764

**Knob Specification Markings:**

Pull turn

**Longest Horizontal Distance Between Mounting Centers:**

1.865 inches single mounting facility and 1.885 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Actuator knob and metallic inclosure and pull to turn and cam actuated

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator and counterclockwise single actuator

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Threaded stud

**Contact Switching Action:**

Makes before breaks, breaks before makes single section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

3.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0