NSN 5930-00-791-7297

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-791-7297

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Driptight and oiltight and watertight
Overall Height:
2.688 inches
Actuator Length:
2.000 inches
Actuator Style:
Roller arm
Actuator Height:
0.500 inches
Actuator Roller Diameter:
0.625 inches
Actuator Roller Width:
0.250 inches
Housing Height:
2.188 inches
Housing Length:
3.875 inches
Housing Width:
1.438 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
3.500 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.062 inches
Maximum Voltage Rating In Volts:
240.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, one position momentary single switch unit
Switch Release Force:
44.0 inch-ounces
Switch Actuating Force:
44.0 inch-ounces
Actuator Movement:
5.0 pretravel degrees and 25.0 overtravel degrees and 5.0 differential degrees

100.000 milliamperes resistive dc

Contact Load Current Rating At Maximum Rated Voltage:

Precious Material And Location:

Contacts silver

NSN 5930-00-791-7297

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0