

View Online at <https://aerobasegroup.com/nsn/5930-00-792-2910>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.650 inches

Overall Height:

2.000 inches

Overall Width:

2.350 inches

First Flat Length:

0.560 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.620 inches single actuator

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.250 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

0.625 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

Shortest Vertical Distance Between Mounting Centers:

0.625 inches single mounting facility

Operating Temperature Range:

+0.0/+185.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

3 each section rear

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

118.0 ac at sea level

Mounting Facility Pattern:

Four position diamond single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0