

View Online at <https://aerobasegroup.com/nsn/5930-00-792-2929>

**Thread Class:**

2b single mounting facility

**Overall Length:**

3.150 inches

**Overall Height:**

1.750 inches

**Overall Width:**

1.750 inches

**First Flat Length:**

0.560 inches single actuator

**Flat Height:**

0.219 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.620 inches single actuator

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.250 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

0.625 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.250 inches single mounting facility

**Shortest Vertical Distance Between Mounting Centers:**

0.625 inches single mounting facility

**Operating Temperature Range:**

+0.0/+185.0 degrees fahrenheit

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

16 single section rear

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.138 inches single mounting facility

**Contact Voltage Rating In Volts:**

118.0 ac at sea level

**Mounting Facility Pattern:**

Four position diamond single mounting facility

**Switch Actuator Indexing Position Quantity:**

16 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Turret

**Contact Switching Action:**

Makes before breaks single section rear

**Switch Actuator Positioning Increment:**

22.5 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load ac at sea level

**Special Features:**

Crosstalk not to exceed 40db down with 2000 ohms between terminals and ground and a 2v rms 2 kc signal applied to any terminal

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0