## NSN 5930-00-792-3536

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-792-3536

**Thread Class:** 

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Explosion proof and moisture proof

**Overall Length:** 

1.625 inches

**Shaft Diameter:** 

0.125 inches single actuator

**Shaft Length:** 

1.000 inches single actuator

**Overall Diameter:** 

0.500 inches

**Individual Section Quantity:** 

1

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section front

**Throw Quantity:** 

4 single section front

**Mounting Method:** 

Threaded bushing single mounting facility

**Features Provided:** 

Metallic inclosure

Thread Size:

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:** 

250.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

5 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Makes before breaks single section front

**Switch Actuator Positioning Increment:** 

36.0 degrees single actuator

## NSN 5930-00-792-3536

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

1.0 amperes resistive load dc at sea level

Style Designator:

Snap or line

**Thread Series Designator:** 

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0