NSN 5930-00-792-3559

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-792-3559

Thread Class:

2b single mounting facility

Overall Length:

2.282 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.938 inches single actuator

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.375 inches single mounting facility

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

End Application:

Se test fixt e/i 03956

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

6 single section rear

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

2 single section

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round single actuator

NSN 5930-00-792-3559Rotary Switch - Page 2 of 2



Terminal Type:
Turret
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Detent Rotational Torque Range:
+0.500/+50.000 inch-pounds single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
4.0 amperes resistive load dc at sea level
Precious Material And Location:
Wipers silver
Precious Material:
Silver
Style Designator:
Tap, square frame
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0