

View Online at <https://aerobasegroup.com/nsn/5930-00-792-5158>

**Thread Length:**

0.422 inches single mounting facility and 0.454 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

Between 2.112 inches and 2.296 inches

**Overall Diameter:**

1.187 inches

**Nonturn Device Radius:**

0.170 inches at 3:00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Slotted bushing at 3:00 o'clock

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes inductive load dc at sea level

**Special Features:**

Additional nonturn device type tab, nonturn device radius 0.375 in. Nom at 3:00 o'clock

**Style Designator:**

Circular wafer, bushing mount

**Test Data Document:**

81349-mil-s-3786/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0