# NSN 5930-00-794-2434

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-794-2434

| Hazardous Locations/environmental Protection:          |  |
|--|--|
| Watertight   |  |
| Overall Length:  |  |
| 5.188 inches   |  |
| Overall Height:  |  |
| 20.187 inches  |  |
| Overall Width:   |  |
| 2.812 inches   |  |
| Body Height:   |  |
| 2.750 inches   |  |
| Unthreaded Mounting Hole Diameter:                     |  |
| 0.281 inches   |  |
| Capillary Tube Length:                                 |  |
| 72.0 inches  |  |
| Bulb Length:   |  |
| 14.500 inches  |  |
| Bulb Diameter:   |  |
| 1.125 inches   |  |
| Longest Horizontal Distance Between Mounting Centers:  |  |
| 2.406 inches   |  |
| Shortest Horizontal Distance Between Mounting Centers: |  |
| 0.656 inches   |  |
| Longest Vertical Distance Between Mounting Centers:    |  |
| 3.281 inches   |  |
| Tempurature Sensing Element Type:                      |  |
| Capillary tube-bulb                                    |  |
| Operating Tempurature Rating:                          |  |
| 157.0 degrees fahrenheit                               |  |
| Mounting Method:                                       |  |
| Bracket and unthreaded hole                            |  |
| Features Provided:                                     |  |
| Electrical access port and manual reset button         |  |
| Contact Action Stimulus:                               |  |
| Increase   |  |
| Mounting Facility Pattern:                             |  |
| Isosceles triangle                                     |  |
| Nonpile-up Contact Arrangement:                        |  |
| 1 pole, single throw, normally open, momentary action  |  |
| Terminal Type:   |  |
| Screw  |  |
| Contact Load Current Rating:                           |  |

16.0 amperes inductive load first voltage8.0 amperes inductive load second voltage4.0 amperes inductive load third voltage3.2 amperes inductive load fourth voltage9.6 amperes inductive load fifth voltage4.8 amperes inductive load sixth voltage2.5 amperes inductive load seventh voltage2.0 amperes inductive load eighth voltage

## NSN 5930-00-794-2434

Thermostatic Switch - Page 2 of 2



#### **Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

### **Contact Adjustment Range:**

+60.00/+130.00 actuation point degrees fahrenheit and +60.00/+130.00 deactuation point degrees fahrenheit

### **Contact Adjustment Type:**

Internal actuation point screw and internal deactuation point screw

### **Contact Voltage Rating In Volts:**

115.0 ac at sea level first voltage230.0 ac at sea level second voltage440.0 ac at sea level third voltage550.0 ac at sea level fourth eighth

| voltage115.0 dc at sea level fifth voltage230.0 dc at sea level sixth voltage440.0 dc at sea level seventh voltage550.0 dc at sea level |
|---|
| voltage   |
| Media For Which Designed:   |
| Gas or liquid   |
| Style Designator:   |
| Rectangular   |
| Shelf Life:   |

**Unit Of Measure:** 

**Demilitarization:** 

No

N/a

Fiig:

A048b0