# NSN 5930-00-796-5577

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-796-5577

# Thread Class:

2a single mounting facility

# Thread Length:

0.250 inches single mounting facility

# **Overall Length:**

3.312 inches

# Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.500 inches single actuator

#### **Overall Diameter:**

1.250 inches

Nonturn Device Radius:

0.500 inches at 12: 00 o'clock

Individual Section Quantity:

4

#### Nonturn Device Type:

Tab at 12: 00 o'clock

# Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section front

## Throw Quantity:

6 each section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### **Rotor Through Connection Quantity:**

1 each section

#### Switch Actuator Indexing Position Quantity:

6 single actuator

# Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes each section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-796-5577

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:

Fixed stop single actuator

#### **Contact Load Current Rating:**

15.0 amperes resistive load dc at sea level

# Precious Material And Location:

Contact surfaces silver

# **Precious Material:**

Silver

# Style Designator:

Tap, circular, bushing mount

# **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A052b0