

View Online at <https://aerobasegroup.com/nsn/5930-00-796-9826>

Thread Class:

3a single pressure connection

Thread Length:

0.500 inches single pressure connection

Overall Length:

4.310 inches

Outside Diameter:

0.500 inches single connection

Overall Width:

3.620 inches

Body Diameter:

3.000 inches

Body Length:

2.560 inches

Unthreaded Mounting Hole Diameter:

0.200 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

14 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

120.00 pounds per square inch

Thread Size:

0.500 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained

Terminal Type:

Wire lead

Contact Load Current Rating:

10.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

20.00 actuation point pounds per square inch and 8.00 deactuation point pounds per square inch and 12.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0